




LVES Home L Series

HOME-ESS-LV-5.12K-M

SMART ENERGY
SUSTAINABLE SOLUTIONS „



Easier Installation

- Ultra-thin body for easy handling
- Intelligent automatic addressing

Higher Performance

- Rapid charge and discharge ability (100A per unit)
- Highest 95% DOD, much more usable energy
- Maximum 200A for main circuit during parallel, no need to install combiner box

Smart Management

- 7/24 real-time monitoring, remote diagnosis and upgrading
- Fast configuration via APP/Platform

Super Safe and Reliable

- Top quality LFP battery
- Thermal aerosol fire protection module for extra protection in the home
- Smart BMS and online-EMS

LVES Home L Series

Model	HOME-ESS-LV-5.12K-M
Nominal Energy	5.12kWh
Nominal Voltage	51.2V
Operating Voltage Range	43.2-57.6V
Cell Type	LFP(LiFePO ₄)
Dimension(W*D*H)	400*139*650mm
Weight	45.5Kg
Charging Temperature	From 0 to 50°C
Discharging Temperature	From -10 to 55°C
Depth of Discharge	95% DOD
Nominal Charge Current	100A
Max. Charge Current	100A
Nominal Discharge Current	100A
Max. Discharge Current	100A
Maximum parallel number	16
Ingree Protection Degree	IP66
Cooling Type	Natural convection
Humidity	≤95%
Warranty	12 years
Communication	CAN/RS485/WIFI/Bluetooth
Battery Safety	IEC 62619/CE-EMC
Transportation Certification	UN38.3

IoT Technology Smart Systematic EMS Based on AI

An all-round platform to power your life

- √ Smart control to optimize your energy allocation
provide 24/7 automatic monitoring
- √ Thoughtful cloud service for preserving batteries
providing remote diagnostics or upgrades
- √ Intelligent technology extends battery life
anticipates and resolves potential problems





202509180002-U




Product Info



Official Website

 info@hanchuess.com  0510-88865288  www.hanchuess.com

 No.9 Huicheng Road,Huishan District,214177 Wuxi, Jiangsu, China